

带 TwinCONTACT 双接线端子的面板式插座
货号 1342




- # 免螺钉弹簧端子
- # 外部固定

技术信息

| | |
|------|-------------------|
| 伏特 | 16 A |
| 极数 | 4 p |
| 电压 | 230 V |
| 钟点位置 | 9 h |
| 赫兹 | 50-60 Hz |
| 连接方式 | 免螺钉 - TwinCONTACT |
| 触点 | 标准 |
| 防护等级 | IP 44 |
| 重量 | 210 克 |
| 认证标志 | VDE, EAC |

图纸



| Drawing 1 MB 463 | Amp. Poles | 16 | | | 32 | | |
|--|---------------|-------------|-------------|-------------|-------------|-------------|-------------|
| | | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 95 | 93 | 92.5 | 102 | 102 | 102 |
| | b | 73.5 | 87.5 | 87.5 | 94 | 94 | 94 |
| | c | 93 | 107.5 | 110 | 115.5 | 115.5 | 119.5 |
| | d | 55.5 | 55.5 | 55.5 | 62 | 62 | 62 |
| | e | 61 | 76 | 76 | 84 | 84 | 84 |
| | f1 | 5.3 | 5.3 | 5.3 | 5.1 | 5.1 | 5.1 |
| | f2 | 5.3 | 5.3 | 5.3 | 5.1 | 5.1 | 5.1 |
| | h | 139 | 139 | 136.5 | 160 | 160 | 156.5 |
| | i | 19.8 | 21.5 | 21.5 | 26.5 | 26.5 | 26.5 |
| | M | M20x | M25x | M25x | M25x | M32x | M32x |
| Terminal for cond. cross section (mm²) min.-max. | | 1.5 1.5 1.5 | 1.5 1.5 1.5 | 1.5 1.5 1.5 | 2.5 2.5 2.5 | 2.5 2.5 2.5 | 2.5 2.5 2.5 |
| | | -4 | -4 | -4 | -6 | -6 | -6 |