

壁装式插座  
货号 27008




- # 带螺钉接线端子
- # 外部固定
- # 从顶部穿入电缆

技术信息

|      |               |
|------|---------------|
| 伏特   | 32 A          |
| 极数   | 5 p           |
| 电压   | 400 V         |
| 钟点位置 | 6 h           |
| 赫兹   | 50-60 Hz      |
| 连接方式 | 螺钉连接          |
| 触点   | 标准            |
| 防护等级 | IP 44         |
| 重量   | 377 克         |
| 认证标志 | VDE, EAC, CQC |

图纸



| Drawing<br>1 MB 463 | Amp.<br>Poles                                    | 16   |       |       | 32    |       |       |
|---------------------|--|------|-------|-------|-------|-------|-------|
|                     |  | 3    | 4     | 5     | 3     | 4     | 5     |
| Dim. in mm          | a  | 95   | 93    | 92.5  | 102   | 102   | 102   |
|                     | b  | 73.5 | 87.5  | 87.5  | 94    | 94    | 94    |
|                     | c  | 93   | 107.5 | 110   | 115.5 | 115.5 | 119.5 |
|                     | d  | 55.5 | 55.5  | 55.5  | 62    | 62    | 62    |
|                     | e  | 61   | 76    | 76    | 84    | 84    | 84    |
|                     | f1   | 5.3  | 5.3   | 5.3   | 5.1   | 5.1   | 5.1   |
|                     | f2   | 5.3  | 5.3   | 5.3   | 5.1   | 5.1   | 5.1   |
|                     | h  | 139  | 139   | 136.5 | 160   | 160   | 156.5 |
|                     | i  | 19.8 | 21.5  | 21.5  | 26.5  | 26.5  | 26.5  |
|                     | M  | M20x | M25x  | M25x  | M25x  | M32x  | M32x  |
|                     | Terminal for cond. cross section (mm²) min.-max. | 1.5  | 1.5   | 1.5   | 1.5   | 1.5   | 1.5   |
|                     |  | 1.5  | 1.5   | 1.5   | 2.5   | 2.5   | 2.5   |
|                     |  | -4   | -4    | -4    | -6    | -6    | -6    |