

Cepex 壁装式插座  
货号 4140




# 带螺钉接线端子  
# 带标记栏

技术信息

|      |          |
|------|----------|
| 伏特   | 32 A     |
| 极数   | 5 p      |
| 电压   | 400 V    |
| 钟点位置 | 6 h      |
| 赫兹   | 50-60 Hz |
| 防护等级 | IP 44    |
| 幼童保护 | false    |
| 重量   | 406 克    |
| 认证标志 | EAC, CQC |

图纸



| Drawing<br>1 MB 317   | Amp.<br>Poles | 16     |        |        | 32     |        |        |
|---|---------------|--------|--------|--------|--------|--------|--------|
|   |               | 3      | 4      | 5      | 3      | 4      | 5      |
| Dim. in mm  | a             | 93     | 93     | 93     | 93     | 93     | 93     |
|   | b             | 90     | 90     | 90     | 90     | 90     | 90     |
|   | c             | 88     | 88     | 88     | 100    | 100    | 100    |
|   | d             | 75     | 75     | 75     | 75     | 75     | 75     |
|   | e             | 73     | 73     | 73     | 73     | 73     | 73     |
|   | f             | 5.5    | 5.5    | 5.5    | 5.5    | 5.5    | 5.5    |
|   | g             | 4.2    | 4.2    | 4.2    | 4.2    | 4.2    | 4.2    |
|   | k             | 34     | 34     | 34     | 34     | 34     | 34     |
|   | y             | 25.5   | 25.5   | 25.5   | 25.5   | 25.5   | 25.5   |
|   | M             | 25x1.5 | 25x1.5 | 25x1.5 | 25x1.5 | 25x1.5 | 25x1.5 |
| Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. |               | 1.5    | 1.5    | 1.5    | 2.5    | 2.5    | 2.5    |
|   |               | -4     | -4     | -4     | -6     | -6     | -6     |