

面板式插头
货号 474




- # 带螺钉接线端子
- # 带铰链翻盖

技术信息

| | |
|------|----------|
| 伏特 | 32 A |
| 极数 | 5 p |
| 电压 | 400 V |
| 钟点位置 | 6 h |
| 赫兹 | 50-60 Hz |
| 连接方式 | 螺钉连接 |
| 触点 | 标准 |
| 防护等级 | IP 67 |
| 重量 | 434 克 |
| 认证标志 | EAC |

图纸



| Drawing | Amp. | 16 | | | | 32 | | 63 | |
|---|------|-------|-----|-----|-----|-----|-----|----|--|
| | | Poles | | 3 | 4 | 5 | 4 | 5 | |
| 2 MB 40 | | 5 | | | | | | | |
| Dim. in mm | a | 85 | 85 | 85 | 85 | 114 | 114 | | |
| | b | 85 | 85 | 85 | 85 | 114 | 114 | | |
| | c | 141 | 141 | 141 | 144 | 180 | 180 | | |
| | d | 70 | 70 | 70 | 70 | 90 | 90 | | |
| | e | 70 | 70 | 70 | 70 | 90 | 90 | | |
| | f | 6.2 | 6.2 | 6.2 | 6.2 | 6.2 | 6.2 | | |
| | g | 6 | 6 | 6 | 6 | 6 | 6 | | |
| | g.1 | 2 | 2 | 2 | 2 | 2 | 2 | | |
| | h | 181 | 181 | 181 | 188 | 242 | 242 | | |
| | s | 86 | 93 | 93 | 100 | 113 | 113 | | |
| | l | 30 | 30 | 30 | 30 | 40 | 40 | | |
| Terminal for cond. cross section (mm ²) min.-max. | 1 | 2.5 | 2.5 | 2.5 | 2.5 | 4 | 4 | | |
| | | -2.5 | -6 | -6 | -6 | -16 | -16 | | |