

壁装式插座
货号 9352




- # 带螺钉接线端子
- # 抗化学腐蚀
- # 带 2 个外部固定孔
- # 外壳基座可旋转 180°
- # 插座可安装辅助触点

技术信息

| | |
|------|----------|
| 伏特 | 32 A |
| 极数 | 3 p |
| 电压 | 400 V |
| 钟点位置 | 9 h |
| 赫兹 | 50–60 Hz |
| 连接方式 | 螺钉连接 |
| 触点 | 标准 |
| 防护等级 | IP 67 |
| 重量 | 510 克 |
| 认证标志 | EAC, CQC |

图纸



| Drawing 1 MB 622 | Amp. Poles | 16 | | | 32 | | |
|--|---------------|----------------------------|------|------|----------------------------|------|------|
| | | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 100 | 100 | 100 | 100 | 100 | 100 |
| | b | 101 | 101 | 101 | 109 | 109 | 109 |
| | c | 117 | 125 | 131 | 157 | 157 | 160 |
| | d | 50 | 50 | 50 | 50 | 50 | 50 |
| | e | 84 | 84 | 84 | 92 | 92 | 92 |
| | f1 | 5.3 | 5.3 | 5.3 | 5.3 | 5.3 | 5.3 |
| | f2 | 5.3 | 5.3 | 5.3 | 5.3 | 5.3 | 5.3 |
| | g | 6.5 | 6.5 | 6.5 | 6.5 | 6.5 | 6.5 |
| | h | 131 | 131 | 132 | 148 | 148 | 148 |
| | i | 24.7 | 24.7 | 24.7 | 27.5 | 27.5 | 27.5 |
| | M | 25 (optional M20) | | | 32 (optional M25) | | |
| | M* | 2x25 (blind) to be cut out | | | 2x25 (blind) to be cut out | | |
| Max. cable diam. (mm) | | 18 (M25) and 15 (M20) | | | 25 (M32) and 18 (M25) | | |
| Terminal for cond. cross section (mm²) min.-max. | | 1.5 | 1.5 | 1.5 | 2.5 | 2.5 | 2.5 |
| | | -4 | -4 | -4 | -6 | -6 | -6 |